

---

```
; USER CONFIG AREA
;;
;; LOAD ADDITIONAL MODULES
;;(load "hideif.el")
;;(load "hideshow.el")
;;(load "completion.el")
;;(load "paren.el")

;;
;; Misc
;;(initialize-completions)
(display-time)

;; SETTING GENERAL VARIABLES
;; Time
(setq display-time t)
(show-paren-mode t)
(blink-cursor-mode nil)

(setq transient-mark-mode t)
(setq default-indicate-buffer-boundaries (quote left))
(setq default-indicate-empty-lines t)

;; Zeilennummer( Spalten anzeigen
(setq line-number-mode t)
(setq column-number-mode t)
(menu-bar-mode t)
(tool-bar-mode nil)

(setq minibuffer-max-depth nil)
(setq ediff-auto-refine-limit 140000)
(setq transient-mark-mode t)
(setq inhibit-startup-message t)
(setq indent-tabs-mode nil)
(setq hilit-auto-highlight-maxout 600000)
(setq compilation-window-height 23)
(set-variable (quote scroll-step) 1)
(global-font-lock-mode 1)
(setq indent-tabs-mode nil)
;; highlight the current line; set a custom face, so we can
;; recognize from the normal marking (selection)
(defface hl-line '((t (:background "#e4e4ce"))))
  "Face to use for `hl-line-face'." :group 'hl-line)
(setq hl-line-face 'hl-line)
(global-hl-line-mode t) ; turn it on for all modes by default

;; no tool bar
(setq transient-mark-mode t)

;; SYNTAX MODES
; Default Indent
(setq c-basic-offset 3)
; No auto-indentation after ;
(setq-default c-electric-flag nil)

(setq c-default-style '((java-mode . "awk")
                        (awk-mode . "awk")))

;; Don't want no TABS
(add-hook 'c++-mode-hook '(lambda() (setq indent-tabs-mode nil)))
(add-hook 'java-mode-hook '(lambda() (setq indent-tabs-mode nil)))
(add-hook 'awk-mode-hook '(lambda() (setq indent-tabs-mode nil)))
(add-hook 'perl-mode-hook '(lambda() (setq indent-tabs-mode nil)))
;; Reindent after "Return"
(add-hook 'c++-mode-hook '(lambda() (define-key c++-mode-map (quote [(return)]) (quote
reindent-then-newline-and-indent))))
(add-hook 'java-mode-hook '(lambda() (define-key java-mode-map (quote [(return)]) (quote
reindent-then-newline-and-indent))))
(add-hook 'awk-mode-hook '(lambda() (define-key awk-mode-map (quote [(return)]) (quote
reindent-then-newline-and-indent))))
(add-hook 'perl-mode-hook '(lambda() (define-key perl-mode-map (quote [(return)]) (quote
reindent-then-newline-and-indent))))
```

---

---

```
;;
;; KEYBOARDS SETTINGS
;; ----- Funktionstastenbelegung -----
(global-set-key (quote [home]) (quote beginning-of-line))
(global-set-key (quote [c-home]) (quote beginning-of-buffer))
(global-set-key (quote [end]) (quote end-of-line))
(global-set-key (quote [c-end]) (quote end-of-buffer))
(global-set-key (quote [(control right)]) (quote forward-word))
(global-set-key (quote [(control left)]) (quote backward-word))
(global-set-key (quote [mouse-3]) (quote kill-region))
(global-set-key [backspace] 'delete-backward-char)
;; F-Keys
(global-set-key (quote [f1]) (quote repeat-complex-command));; F1
(global-set-key (quote [(shift f1)]) (quote indent-region));; Shift-F1
(global-set-key (quote [f2]) (quote save-buffer));; F2
(global-set-key (quote [(shift f2)]) (quote split-window));; Shift-F2
(global-set-key (quote [f3]) (quote find-file));; F3
(global-set-key (quote [(shift f3)]) (quote list-buffers));; F3
(global-set-key (quote [f4]) (quote blink-matching-open))
(global-set-key (quote [(shift f4)]) (quote kill-buffer))
(global-set-key (quote [f5]) (quote compile))
(global-set-key (quote [(shift f5)]) (quote kill-compilation))
(global-set-key (quote [f6]) (quote next-error))
(global-set-key (quote [(shift f6)]) (quote compilation-previous-error))
(global-set-key (quote [f7]) (quote isearch-forward))
(global-set-key (quote [(shift f7)]) (quote query-replace))
(global-set-key (quote [f8]) (quote uncomment-region))
(global-set-key (quote [(shift f8)]) (quote goto-line))
(global-set-key (quote [f9]) (quote comment-region))
(global-set-key (quote [(shift f9)]) (quote comment-region))
(global-set-key (quote [f10]) (quote kill-region))
(global-set-key (quote [(shift f10)]) (quote kill-region))
(global-set-key (quote [f11]) (quote copy-region-as-kill))
(global-set-key (quote [(shift f11)]) (quote describe-variable))
(global-set-key (quote [f12]) (quote font-lock-fontify-buffer))
(global-set-key (quote [(shift f12)]) (quote untabify))
;; More
(global-set-key (quote [(control v)]) (quote yank))
(global-set-key (quote [(control p)]) (quote call_insert))
(global-set-key (quote [(control o)]) (quote decl_insert))
(global-set-key (quote [(control c)]) (quote copy-region-as-kill))
(global-set-key (quote [(control t)]) (quote kill-word))
(global-set-key (quote [(control y)]) (quote kill-line))
(global-set-key (quote [(control a)]) (quote yank))
(global-set-key (quote [(control prior)]) (quote beginning-of-buffer))
(global-set-key (quote [(control next)]) (quote end-of-buffer))

(global-set-key (quote [(meta right)]) (quote hippie-expand))

;; scroll in minibuffer history with arrow keys
(define-key minibuffer-local-map (quote [(down)]) (quote next-history-element))
(define-key minibuffer-local-map (quote [(up)]) (quote previous-history-element))

;; Mouse Actions
(define-key global-map (quote [(control mouse-1)]) (quote mouse-buffer-menu))
(define-key global-map (quote [(c-down-mouse-1)]) (quote mouse-buffer-menu))
(global-set-key (quote [(mouse-3)]) (quote kill-region))
(global-set-key (quote [(mouse-2)]) (quote mouse-yank-at-click))

;; Look
;(set-background-color "#dedede")
;(set-background-color "#ccccca")
;(set-foreground-color "#22222a")
;; Colours
(font-lock-mode)
(set-face-foreground (quote font-lock-string-face) "DarkGreen")
(set-face-foreground (quote font-lock-comment-face) "DarkBlue")
(set-face-foreground (quote font-lock-keyword-face) "white")
(set-face-foreground (quote font-lock-function-name-face) "Brown")
(set-face-foreground (quote font-lock-variable-name-face) "DimGray")
(set-face-foreground (quote font-lock-type-face) "IndianRed")
```

---

---

```
(set-face-background (quote region) "Cyan")
(set-face-background (quote modeline) "Brown")
(set-face-foreground (quote modeline) "white")

;; Some Scrolling Hacks

;;(set-frame-font "Lucida Console")

;; USER CONFIG AREA END
;; No Manual Changes below this Point

(custom-set-variables
  ;; custom-set-variables was added by Custom.
  ;; If you edit it by hand, you could mess it up, so be careful.
  ;; Your init file should contain only one such instance.
  ;; If there is more than one, they won't work right.
  '(blink-cursor-mode nil)
  '(column-number-mode t)
  '(display-time-mode t)
  '(show-paren-mode t))
```

---